




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: B60D 1/06, 1/52		A1	(11) International Publication Number: WO 97/22484
			(43) International Publication Date: 26 June 1997 (26.06.97)
(21) International Application Number: PCT/US96/18473		(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 18 November 1996 (18.11.96)			
(30) Priority Data: 08/575,417 20 December 1995 (20.12.95) US		Published With international search report.	
(71) Applicant: REESE PRODUCTS, INC. (US/US); 51671 State Road, 19 North, Elkhart, IN 46515 (US).			
(72) Inventors: DUVERNAY, Mark, E.; 2100 East Bristol, H232, Elkhart, IN 46514 (US). MATER, Robert, F., Jr.; 1865 Greenleaf Boulevard, Elkhart, IN 46514 (US). MELLOW, James, A.; 1336 North Cranbrook Road, Bloomfield Hills, MI 48301 (US).			
(74) Agents: SCHICKLI, Warren, D. et al.; King and Schickli, Suite 210, 3070 Harrodsburg Road, Lexington, KY 40503 (US).			

(54) Title: TRAILER HITCH RECEIVER WITH HITCH BALL LOCK



(57) Abstract

A trailer hitch (10) includes a hitch bar (12), a ball mount head (14), a hitch ball (18) with a threaded mounting stem (24) and a fastener (28) for securing the hitch ball to the ball mount head. More specifically, the ball mount head (14) includes a mounting aperture (20) with a sidewall (21) defining an acircular outline. The mounting stem (24) of the hitch ball (18) includes a locking element (22) for engaging within the sidewall (21) defining the acircular outline. As a result of this structural relationship, rotation of the hitch ball mounting stem (24) relative to the ball mount head (14) is prevented so that the fastener (28) may be easily secured thereto and tightened to hold the hitch ball in position.